

FT-376 Drain Slot Router

ROUTERS & DRILLS » FT-376

- Mills water drain slots and opens ventilation holes on PVC profiles at various angles.
- Two frequency controlled (inverter) high speed motors mills drain slots on different surfaces of the profile.
- Motors can work individually. Routing speeds can be adjusted independently.
- Easy to adjust according to different profile cross sections.
- The upper routing unit automatically positions itself to left or right side of the profile.
- Pneumatic profile clamping.



FT-386 Drain Slot Router

ROUTERS & DRILLS » FT-386

- Mills water drain slots and opens ventilation holes on PVC profiles at various angles.
- Three frequency controlled (inverter) high speed motors mills drain slots on different surfaces of the profile.
- Motors can work individually. Routing speeds can be adjusted independently.
- Easy to adjust according to different profile cross sections.
- The upper routing unit automatically positions itself to left or right side of the profile.
- Pneumatic profile clamping.



Technical Features :

• Power Supply : 230 V, 50-60 Hz	• Air Consumption: 18 l/min.
• Total Power Output: 0,8 kW	• Machine Height: 1260 mm
• Power Output of Each Motor: 0,37 kW	• Machine Length: 800 mm
• Router Spindle Speed: 18000 rpm	• Machine Width: 760 mm
• Max.Routing Length : 50 mm	• Machine Weight: 95 kg
• Stroke : 25 mm	
• Max. Profile Section Dimensions: 90 mm x 90 mm	
• Air Pressure: 6-8 bar	

Technical Features :

• Power Supply : 230 V, 50-60 Hz	• Air Consumption: 24 l/min.
• Total Power Output: 1,2 kW	• Machine Height: 1260 mm
• Power Output of Each Motor: 0,37 kW	• Machine Length: 800 mm
• Router Spindle Speed: 18000 rpm	• Machine Width: 760 mm
• Max.Routing Length : 50 mm	• Machine Weight: 102 kg
• Stroke: 25 mm	
• Max. Profile Section Dimensions: 90 mm x 90 mm	
• Air Pressure: 6-8 bar	