



## KT-805 Sash Assembly Machine

**ASSEMBLY MACHINES » KT-805** 

- Serial and high quality standard assembly of single or tilt and turn opening system window and door sashes in various dimensions.
- By combining of different processes at one table, sash assembly duration is shortened.
- Punch unit for cropping the single or tilt and turn espagnolettes as well as scissor hinges according to sash dimension without measuring.
- Automatic screwing unit with height adjustment for espagnolette, scissor hinges.
- Drilling of hinge holes via measuring apparatus which standardizes the process.
- The work table can be shifted 15° for ergonomic working.
- Standard equipped with shelves for hardware and other tools.



## RATIN

## **Technical Features :**

<ul> <li>Power Supply: 230V, 1~ 50-60 Hz</li> </ul>	Screw Length:: 10-35 mm	
Total Power Output: 100W, 1,5A	Air pressure: 6-8 bar	
• Min. Frame Size: 250 mm x 250 mm	Machine Height: 2150 mm	
Max. Frame Size: 2400 mm x 2100 mm	Machine Length: 3500 mm	
Max. Profile Height: 90 mm	Machine Width: 2880 mm	
Min. Profile Width: 42 mm	Machine Weight: 800 kg	
Max. Profile Width : 100 mm		
Screw Head Diameter : 5-9,8 mm		